

01.04 lin m **Safety sealing tape**€/lin m€

Product:

Manufacturer:

.....
or equivalent, to be inserted in corners
and connection areas of wall/floor into the fresh
knifing filler; overlaps to be carried out carefully;
glued in sealing tape to be filled over by fresh
sealing compound.

02.00 Tiling work

02.01m² **Wall tiles**€/m²€

Wall lining of stoneware DIN-EN 159 /
stoneware DIN-EN 176

Manufacturer: Porcelaingres

Product:

Size:

Article No.:

To be installed in thin-bed acc. to DIN 18157
by means of a plastic hardened hydraulic
thin-bed mortar on existing surface. Tiles shall
be installed from upper edge of floor to a height
of ... m/lower edge of ceiling, joint width 2 – 3 mm.
Jointing work of the lining in joint colour ... with a
plastic hardened hydraulic mortar shall be included
in the unit price.

02.02pcs. **Decorative wall tiles**€/pce.€

Decorative wall tiles matching with Item ...
to be supplied and installed.

Manufacturer: Porcelaingres

Product:

Size:

Article No.:

02.03 Floor tiles

02.03.1m² Installation of floor lining of ceramic€/m²€

tiles, unglazed, on floating cement
anhydrite floor acc. to DIN 18560

Manufacturer: Porcelaingres

Product:

Size:

Surface:

Article No.:

Tiles: Dry pressed ceramic tiles group B1 EN178,
unglazed fine stoneware, water absorption ≥ 0,05 %,
size allowance ± 0.2% (± 5.0% thickness)

Note: The technical characteristics of alternatively offered material shall be comparable to those of the materials specified in the bidding documents.

To be installed in thin-bed acc. to DIN 18157 by means of a plastic hardened hydraulic thin-bed mortar; joint width 2-3 mm.

The slabs are installed with cut joints/semi-bond/... bond with a joint width of 2-3 mm. Jointing work in joint colour ... with a plastic hardened hydraulic finished-joint mortar shall be included in the unit price.

Note: Accounting will be according to surface installed, thus scraps must be calculated and included and/or the subsequent items shall be taken into consideration.

02.03.2m² **Installation of flooring of ceramic tiles,**€/m²€

unglazed, as composite flooring on reinforced concrete ceiling/concrete base/cement screed acc. to DIN 18560 as levelling screed by vibration method as individual tile in cm thick mortar bed on average acc. to VOB DIN 18352, strength acc. to ZE 20 / ZE 30 acc. to DIN 18560.

Manufacturer: Porcelaingres
Product:
Size:
Surface:
Article No.:

Tiles: Dry pressed ceramic tiles group B1 EN178, unglazed fine stoneware, water absorption $\geq 0,05$ %, size allowance $\pm 0.2\%$ ($\pm 5.0\%$ thickness)

Note: The technical characteristics of alternatively offered material shall be comparable to those of the materials specified in the bidding documents.

Prior to the beginning of installation work, the surface shall be carefully cleaned, moistened and laitance shall be provided as contact layer. The tiles shall be installed acc. fresh mortar bed and vibrated by a machine. The joints shall be filled in joint colour by sprinkling the lining with a hydraulic finished joint mortar and shall be included in the unit price.

Note: Accounting will be according to surface installed, thus scraps must be calculated and included and/or the subsequent items shall be taken into consideration.

02.03.3		Extra charge for floor tile of Item for		
	% portion (Total of items with extra charge)		
02.03.4		Extra charge for each 20 mm additional thickness of mortar bed of Item.		
	% portion (Total of items with extra charge)		
02.03.5pcs.	Decorative floor tiles Decorative floor tiles matching with Item. to be supplied and installed Manufacturer: Porcelaingres Product: Size: Article No.:€/pce.€
02.03.6pcs.	Skirting tiles, rounded Wall connection as grooved or vertical skirting matching with floor tiles of Item. To be installed in thin bed acc. to DIN 18157 by means of a hydraulic thin-bed mortar Manufacturer: Porcelaingres Product: Size: Article No.: Tiles: Dry pressed ceramic tiles group B1 EN178, unglazed fine stoneware, water absorption ≥ 0,05 %, size allowance ±0.2% (± 5.0% thickness)€/pce.€
		Note: The technical characteristics of alternatively offered material shall be comparable to those of the materials specified in the bidding documents.		
		Jointing work at the skirting in joint colour ... with a plastic hardened hydraulic mortar shall be included in the unit price.		
02.03.7pcs.	Stairs Stairs to floor tiles of Item. to be installed in thin bed acc. to DIN 18157 by means of a hydraulic thin-bed mortar Manufacturer: Porcelaingres Product: Size: Design: Article No.:€/pce.€
		Note: The technical characteristics of alternatively offered material shall be comparable to those of the materials specified in the bidding documents.		

Jointing work at the skirting in joint colour ... with a plastic hardened hydraulic mortar shall be included in the unit price.

03.0		Joint sealing work/settlement joints	
03.01lin m	Flexible connection joints (connection wall/floor)€/lin m€
		Flexible connection joint between wall and floor lining/skirting and flooring as permanently flexible joints, width ... mm to be provided by means of a permanently flexible putty based on silicon; colour extra charge.	
		Three-flank adhesion of putty shall be excluded by installing a round PE chord. Supply and installation of the round PE chord and clean cutting of insulation strip at edge level shall be included.	
03.02lin m	Flexible connection joints of internal corners€/lin m€
		Flexible connection joints of internal corners of rooms as permanently flexible joints width mm to be provided by means of a permanently flexible putty based on silicon.	
03.03lin m	Panel limitation joints€/lin m€
		Flexible panel limitation joints as permanently flexible joints width mm to be provided by means of a permanently flexible putty based on silicon; colour ... extra charge.	
		Three-flank adhesion of putty shall be excluded by installing a round PE chord. Supply and installation of the round PE chord and clean cutting of insulation strip at edge level shall be included.	
03.03.1lin m	Panel limitation joint section€/lin m€
		Panel limitation joint section for mechanically highly stressed lining to be supplied and installed at both sides of the panel limitation joints as specified by the manufacturer.	
		Fastening means to fastening at substructure shall be included in the calculation.	
03.03.2lin m	Settlement section€/lin m€
		Settlement section for mechanically highly stressed lining to be supplied and installed at both sides of the panel limitation joints as specified by the manufacturer.	
		Fastening means to fastening at substructure shall be included in the calculation.	

03.04lin m **Nosing section (Schlüter sections)**€/lin m€
 Nosing sections along the panel limitation joints of Item.
 as Schlüter rails of with
 h = mm to be supplied as extra charge and to be installed as specified by the manufacturer.

03.05lin m **Nosing section**€/lin m€
 (Adhesive nosing section of V4A steel) at external corners as protection of the ascending edges to be supplied and installed as specified by the manufacturer.

Manufacturer:
 Dimensions: Length:
 Section:

The processing instructions of the manufacturer shall be followed.

04.00 Cleaning, impregnation

04.01m² **Basic cleaning**€/m²€
 Basic cleaning of flooring of Item. by means of to be carried out properly.

Basic cleaning should be carried out after a period of 4 days after installation of the flooring at the earliest.

The processing instructions of the manufacturer shall be followed.

04.02m² **Impregnation**€/m²€
 Impregnation of the flooring of unglazed polished tiles of Item. by means of

The impregnation shall be applied on the clean and dry flooring immediately after the basic cleaning.

The processing instructions of the manufacturer shall be followed.